

F780 HC Series

A High Performance Antimicrobial Bar Code Linear Scanner
for Sterile and Hygiene-sensitive Applications

Disinfectant-ready enclosure
incorporated with antimicrobial
additives

Comply with JIS Z2801 : 2000
standard

Ruggedized over-mold design to
withstand multiple drops to
concrete from 1.8 meter

GS1 DataBar, PDF, MicroPDF and
composite code support

Outstanding reading capability
on 3 mil barcode with more than
2" depth of field

More than 24" reading distance
on general barcodes

Unsurpassed readability on low
contrast, smudged, poorly-printed
or damaged barcodes

Superior motion tolerance for
rapid and accurate data-capture
on the move

High speed scanning rate up to
500 scans per second for snappy
barcode capture

All-in-one host interface design,
including USB HID, USB COM,
PS/2 keyboard wedge and RS232

Built-in vibrator for noisy working
environment



Society is more germ-conscious than ever. It's a trend to use devices incorporated anti-microbial materials for some specific environments to minimize the risk of spreading infectious micro-organisms and other bacteria.

PCW is committed to providing excellent bar code scanner that addresses the needs of those applications. The newly developed CINO antimicrobial F780 scanner not only inherits the outstanding reading performance and reliability of F780, but also protects your customer's safety under complete infection control.

Incorporated antimicrobial additives

The antimicrobial F780 scanner's housing is incorporated with silver inorganic antimicrobial agent, it will not be worn off during its lifetime. This provides an extra layer of protection against the multiplication and spread of potentially harmful microorganisms such as bacteria and microbes on the scanner plastic enclosure surface.

Disinfectant-Ready enclosures

The antimicrobial F780 scanner is designed with disinfectant-ready housing, it allows the plastic to be cleaned or wiped-down with commonly-used cleaning solutions in healthcare environments without harming the housing or the sensitive scanning components inside.

Solution for hygiene-sensitive environments

It can serve a wide range of specific applications where hygiene environment is paramount and high-level safety is vital, such as healthcare, pharmaceutical, cosmetic, food industries, medical laboratories and other sterile environments.

Specifications

Performance Characteristics

Optical System	High performance Linear Imaging Engine
Print Contrast	20% minimum reflective difference
Minimum Resolution	Typical 3 mil (Code 39, PCS 0.9)
Working Distance ¹	More than 16 inches on 100% UPC/EAN symbols More than 24 inches on 20 mil Code 39
Light Source	630nm visible red LED
Scan Rate	Dynamic scanning rate up to 500 scans per second
Reading Direction	Bi-directional (forward and backward)
Pitch/Skew	± 65 ° / ± 65 °
Operating Modes	Toggle, Trigger, Force, Level, Flash, Diagnostic Alternative, Low power, Presentation
Host Interfaces	PC/AT, PS/2 (DOS V) keyboard wedge PC/AT, PS/2 (DOS V) keyboard direct link TTL RS232 serial USB HID (USB Keyboard) USB COM port emulation Laser emulation and Wand emulation
Configuration Setup	Bar code command Windows utility - FuzzyScan PowerTool
Data Editing	Condensed DataWizard via bar code command Full-feature DataWizard via FuzzyScan PowerTool
User Interfaces	3 LEDs for power, good read and status indications Programmable beeper Vibrator

Supported Symbolologies

1D Linear	Code 39, Code 39 Full ASCII, Code 32, Code 39 Trioptic Code 128, UCC/EAN-128, Codabar, Code 11, Code 93 Standard & Industrial 2 of 5, Interleaved & Matrix 2 of 5 German Postal Code, China Postal Code, IATA UPC/EAN/JAN, UPC/EAN/JAN with Addendum Telepen, MSI/Plessey & UK/Plessey GS1 DataBar (formly RSS) Linear, Linear-stacked
Linear-stacked	PDF417, Micro PDF417, Codablock, Composite (available for F788-HC only)

User Environment

Drop Specifications	Withstand multiple 1.8m/6ft. drops to concrete
Environmental Sealing	IP41
Operating Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage Temperature	-40 °C to 70 °C (-40 °F to 158 °F)
Humidity	5% to 95% related humidity, non-condensing
Ambient Light Immunity	0 ~ 100,000 lux
ESD Protection	Functional after 15kV discharge
Recommend cleaning solutions	Gentle dish soap water or alcohol solvent

1. The working distances are measured in 400lux office environment using Grade A bar codes.
2. Don't stare into the LED beam.

Physical Characteristics

Dimension	97.8 mm (L) x 70.5 mm (W) x 156.2 mm (D) 3.85 in. (L) x 2.77 in. (W) x 6.15 in. (D)
Weight	157g (cable excluded)
Color	Plastic: Healthcare White Over-mold: Light Blue
Antimicrobial Additives	Silver inorganic antimicrobial agent
Input Voltage	5VDC ± 10%
Current	Operating : Typical 180 mA @5VDC Standby : Typical 80 mA @5VDC

Safety & Regulatory

EMC	CE, FCC, BSMI, C-Tick, KC, VCCI
Safety ²	LED Eye Safety IEC62471, Exempt Group
Environmental	Compliant with RoHS directive
Antimicrobial	JIS Z2801 : 2000

Accessories

Cables	PS/2 (DOS V) Keyboard Wedge Cable RS232 Serial Cable USB Cable USB Power Steal Cable
Others	Hand-free SmartStand Universal Holder

Accessories



Colors Available : ■ black ■ light gray